

LIFT-UP SYSTEM HOOD

Energy Class: A Black glass

PERFORMANCE

Automatic opening of filtering surface Suction power up to 760 m³ / h 4 suction levels Auto-off Filter saturation indicator Suction operation with filter predisposition Sound power from 38 to 68 dBA

FEATURES

Touch controls LED lighting Internal aluminium grease filters Minimum air outlet Ø 150 mm Non-return air valve (suction)

SERIES ACCESSORIES

Power Cord

OPTIONAL ACCESSORIES

FCHF 9: carbon filter for filtering version




BLACK GLASS FDDH 900 TRC BK

FULGOR MILANO

VENTILATION





| | FDDH 900 TRC BK |
|-------------------------------------|---|
| Туре | Downdraft |
| Finishing | Black glass |
| Installation | Flush top |
| Special feature | Lift |
| FEATURES | |
| Energy efficiency class | A |
| Speed levels | 4 |
| Automatic cut-off | - |
| Grease filter reset warning light | · · |
| Charcoal filter reset warning light | |
| Lighting type | Strip LED |
| Grease filters material | Alluminium |
| Dishwashable grease filters | • |
| Ø duct diameter | Ø 150 mm / rectangular 220 x 90 (230 x 80) |
| Non return flap | • |
| CONTROLS | |
| Programming non return flap | Touch control |
| Remote control | • |
| POWER RATINGS | |
| Output m ³ /h (max) | 757 |
| Sound level (dBA) | 42 - 59 |
| Yearly energy cinsumption (kWH) | 45 |
| Motor power (W) | 275 |
| Tension and frequency (V-Hz) | 220 - 240 / 50 - 60 |
| Power cord lenght (m.) | 2 |
| ACCESSORIES | |
| Motor | · · |
| HP filter for filtering version | FCHF 9 (x 2) |
| DIMENSIONS | |
| Width mm | 900 |
| Height mm | 300 |
| Depth mm | 79 |