INDUCTION HOB 90



# FCLH 9008 ID WT BK



Flush Top Installation



Semi - Flush Top Installation



Wave Touch Slider



Glass Ceramic Surface



Temperature Sensor



Residual Heat System



Booster



Timer



Flexi Zone



Pan Detection System

#### **INDUCTION HOB**

Cera Black ceramic surface

### **PERFORMANCE**

Chef Function
8 cooking areas
Flexi combination for extra-large pots
Booster for rapid heating
Automatic heating
"Pause and Recall" function
Keep warm function
End-of-cooking timer

#### **FEATURES**

3.5" central Wave Touch display Direct interactivity Slider touch controls

#### **SAFETY**

Pans detection sensor Safety switch (accidental use prevention) Residual heat indicator (H) Automatic shutdown with temperature sensor

## **INCLUDED ACCESSORIES**

Scraper for surface cleaning




CERABLACK FCLH 9008 ID WT BK

fulgor-milano.com FULGOR MILANO

# **FULGOR MILANO**

INDUCTION HOB





	FCLH 9008 ID WT BK
Туре	8 cooking zone
Finishing	CeraBlack
INDUCTION PERFORMANCES	
Octa Ø 290 / 180 DUAL	1400 / 2100 ( x8 ) W
Zone flexi	•
Max absorbed power (W)	11040 W
Preloaded temperatures 42 ° C Melting	-
70 ° C Slow cooking	4000 W
90 ° C Simmer	1750 W
INDUCTION COMMANDS	
Programming	Wave Touch
AUTO cooking	•
Timer	•
Residual Heat Indication ( H )	•
Warning indicator sound / Pan detector	-/•
Lock safety key	•
Power levels n.	9 + P
Visual digit display	•
HOOD FEATURES	
Energy efficiency class	-
Levels of aspiration	-
Delayed auto shut-off	-
Grease filter saturation indicator	-
HP filter replacement light	-
Grease filters with oil / type collection	-
Dishwasher safe grease filters	-
Minimum Ø air discharge	-
Air flow non-return FLAP	-
HP filter for filter (optional)	-
AUTO opening (2 steps)	-
Commands	-
Extractive capacity up to m3 / h	-
Noise emissions (dBA)	-
Estimated annual consumption (kWH)	-
BRHM Motor (W)	-
ACCESSORIES	
Scraper	•
Cord	
DIMENSIONS	
Width mm	914
Height mm	48
Depth mm	522
Cut-out (W x D) mm	902 x 500

fulgor-milano.com FULGOR MILANO